



AOS
SEMICONDUCTOR

产品规格说明书

Product Data Sheet

AOS2323XUTQK10

WEB | www.aossemi.cn 



电源管理IC



通信接口芯片




二三极管



LDO稳压器



逻辑器件



MOSFETs



运算放大器



显示驱动



MCU单片机



光电器件



Ultra Low ON-Resistance, Low Voltage, Dual, SPDT Analog Switch

DESCRIPTIONS

The AOS2323 is a dual, low on-resistance, single-pole double-throw (SPDT) analog switch that is designed to operate from 1.8 V to 5.5 V.

The AOS2323 device can handle both analog and digital signals. It features fast switching speeds (50ns) and low on-resistance (0.6 Ω TYP).

Applications include signal gating, chopping, modulation or demodulation (modem), and signal multiplexing for analog-to-digital and digital-to-analog conversion systems.

FEATURES

- 3dB Bandwidth: 30MHz
- ★ High Speed, Typically 50ns
- ★ Supply Range: +1.8V to +5.5V
- ★ Low ON-State Resistance, 0.6 Ω (TYP)
- ★ Break-Before-Make Switching
- ★ Rail-to-Rail Operation
- ★ TTL/CMOS Compatible
- ★ Extended Industrial Temperature Range: -40°C to +125°C


APPLICATIONS

- Wearable Devices
- Battery-Operated Equipment
- ★ Signal Gating, Chopping, Modulation or Demodulation (Modem)
- ★ Portable Computing
- ★ Cell Phones

FUNCTION TABLE

LOGIC	NO	NC
0	OFF	ON
1	ON	OFF

PIN CONFIGURATIONS



PIN DESCRIPTION

NAME	PIN	FUNCTION
V+	1	Power Supply
NO1, NO2	2, 10	Normally-Open Terminal
COM1, COM2	3, 9	Common Terminal
IN1, IN2	4, 8	Digital Control Pin
NC1, NC2	5, 7	Normally-Closed Terminal
GND	6	Ground



ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

V+, IN to GND.....	-0.3V to 7.0V
Analog, Digital Voltage Range ⁽²⁾	- 0.3 to (V+) + 0.3V
Continuous Current NO, NC, or COM.....	±500mA
Peak Current NO, NC, or COM.....	±800mA
Storage Temperature	-65°C to +150°C
Operating Temperature	-40°C to +125°C
Junction Temperature.....	150°C
Package Thermal Resistance @ T _A = +25°C	
SOT23-5, SOT23-6.....	200°C/W
MSOP-10, SOIC-8 ,TSSOP-8.....	150°C/W
SOIC-14, TSSOP-14.....	100°C/W
Lead Temperature (Soldering, 10s)	260°C
ESD Susceptibility	
HBM	1000V
MM	100V



ESD SENSITIVITY CAUTION

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.


- (1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.
- (2) Input terminals are diode-clamped to the power-supply rails. Input signals that can swing more than 0.3V beyond the supply rails should be current-limited to 10mA or less.

PACKAGE/ORDERING INFORMATION

PRODUCT	ORDERING NUMBER	TEMPRANGE	PACKAGE	PACKAGE MARKING	TRANSPORT MEDIA, QUANTITY
AOS2323	AOS2323XUTQK10	-40 -125	QFN-1.4x1.8-10L	2323X	Tape andReel , 3000

NOTE: X = Date Code

MARKING INFORMATION





ELECTRICAL CHARACTERISTICS

V₊ = 5.0V, T_A = -40°C to 125°C (unless otherwise noted)

PARAMETER	SYMBOL	CONDITIONS	V ₊	T _A	MIN	TYP	MAX	UNITS
ANALOG SWITCH								
Analog Signal Range	V _{NO} , V _{NC} , V _{COM}			FULL	0		V ₊	V
On-Resistance	R _{ON}	0 (V _{NO} or V _{NC}) V ₊ , I _{COM} = -10mA, Switch ON, See Figure 1	5V	+25		0.6	1.0	
				FULL			1.2	
			3.3V	+25		1.0	1.5	
				FULL			1.7	
On-Resistance Match Between Channels	R _{ON}	0 (V _{NO} or V _{NC}) V ₊ , I _{COM} = -10mA, Switch ON, See Figure 1	5V	+25		0.04	0.1	
				FULL			0.12	
			3.3V	+25		0.04	0.1	
				FULL			0.12	
On-Resistance Flatness	R _{FLAT(ON)}	0 (V _{NO} or V _{NC}) V ₊ , I _{COM} = -10mA, Switch ON, See Figure 1	5V	+25		0.18	0.3	
				FULL			0.4	
			3.3V	+25		0.54	0.7	
				FULL			0.8	
NC, NO OFF Leakage Current	I _{NC(OFF)} , I _{NO(OFF)}	V _{NO} or V _{NC} = 0.3V, V ₊ /2V _{COM} = V ₊ /2, 0.3V See Figure 2	1.8 to 5.5V	FULL			1	μA
NC, NO, COM ON Leakage Current	I _{NC(ON)} , I _{NO(ON)} , I _{COM(ON)}	V _{NO} or V _{NC} = 0.3V, Open V _{COM} = Open, 0.3V See Figure 2	1.8 to 5.5V	FULL			1	μA
DIGITAL CONTROL INPUTS⁽¹⁾								
Input High Voltage	V _{INH}		5V	FULL	1.5			V
			3.3V	FULL	1.3			V
Input Low Voltage	V _{INL}		5V	FULL			0.6	V
			3.3V	FULL			0.5	V
Input Leakage Current	I _{IN}	V _{IN} = V _{IO} or 0	1.8 to 5.5V	FULL			1	μA

(1) All unused digital inputs of the device must be held at V_{IO} or GND to ensure proper device operation.






ELECTRICAL CHARACTERISTICS(continued)

V₊ = 5.0V, TEMP= - 40°C to 125°C (unless otherwise noted))

PARAMETER	SYMBOL	CONDITIONS	V ₊	TEMP	MIN	TYP	MAX	UNITS
DYNAMIC CHARACTERISTICS								
Turn-On Time	t _{ON}	V _{COM} = V ₊ , R _L = 300 , C _L = 35pF, See Figure 5	5V	+25		50		ns
			3.3V			50		
Turn-Off Time	t _{OFF}	V _{COM} = V ₊ , R _L = 300 , C _L = 35pF, See Figure 5	5V	+25		15		ns
			3.3V			17		
Break-Before-Make Time Delay	t _{BBM}	V _{NO1} =V _{NC1} = V _{NO2} =V _{NC2} = 3V, R _L = 300 , C _L = 35pF, See Figure 6	5V	+25		10		ns
			3.3V			11		
Off Isolation	O _{ISO}	R _L = 50 , Switch OFF, See Figure 8		+25		-68		dB
					f = 100KHz			
				+25		-86		dB
-3dB Bandwidth	BW	Switch ON, R _L = 50 See Figure 7		+25		30		MHz
NC, NO OFF Capacitance	C _{NC(OFF)} , C _{NO(OFF)}	V _{NC} or V _{NO} =V ₊ /2 or GND, Switch OFF See Figure 4		+25		80		pF
NC, NO, COM ON Capacitance	C _{NC(ON)} , C _{NO(ON)} , C _{COM(ON)}	V _{NC} or V _{NO} =V ₊ /2 or GND, Switch ON See Figure 4		+25		350		pF
POWER REQUIREMENTS								
Power Supply Range	V ₊			FULL	1.8		5.5	V
Power Supply Current	I ₊	V _{IN} = GND or V ₊	5.5V	FULL			1	μA



TYPICAL CHARACTERISTICS





Parameter Measurement Information




Figure 1.ON-State Resistance (r_{on})




Figure 2.OFF-State Leakage Current ($I_{COM(OFF)}$, $I_{NO(OFF)}$)




Figure 3.ON-State Leakage Current ($I_{COM(ON)}$, $I_{NO(ON)}$)




Figure 4. Capacitance (C_i , $C_{COM(OFF)}$, $C_{COM(ON)}$, $C_{NO(OFF)}$, $C_{NO(ON)}$)




Figure 5. Turn-On (t_{ON}) and Turn-Off Time (t_{OFF})




Figure 6. Break-Before-Make Time (t_{BBM})




Figure 7. Bandwidth (BW)




Figure 8. OFF Isolation (O_{iso})






Figure 9. Crosstalk (X_{TALK})





PACKAGE OUTLINE DIMENSIONS
QFN-1.4x1.8-10L

