



**AOS**  
**SEMICONDUCTOR**

## 产品规格说明书

Product Data Sheet

AOS138Xx

WEB | [www.aossemi.cn](http://www.aossemi.cn) 



电源管理IC



通信接口芯片



二三极管



LDO稳压器



逻辑器件



MOSFETs



运算放大器



显示驱动



MCU单片机



光电器件



## AOS138 3-Line to 8-Line Decoders/Demultiplexers Inverting and Noninverting

### DESCRIPTIONS

The AOS138, a three to eight decoders/demultiplexers, is designed for 2V to 5.5V operation.

The AOS138 is consist of three enable inputs (E3, E2 and E1), three binary weighted address inputs (A0, A1 and A2) and eight outputs (Y0 to Y7). Among all enable inputs, one is active high output enable (E3) and two are active low output enables (E2 and E1). When the outputs are gated by any of the strobe inputs, they are all forced into the high state. When the outputs are not disabled by the strobe inputs, only the selected output is low while all others are high.

The AOS138 is available in Green SOP16 and TSSOP16 packages. It operates over an ambient temperature range of -40°C to +125°C.

### FEATURES

- Operating Voltage Range: 2V to 5.5V
- Low Power Consumption: 160µA (Max)
- I/O Port or Memory Selector
- Three Enable Inputs to Simplify Cascading
- Balanced Propagation Delay and Transition Times
- Operating Temperature Range: -40°C to +125°C
- Inputs Accept Voltage to 5.5V
- Micro Size Packages: SOP16, TSSOP16

### APPLICATIONS

- LED Displays
- Servers
- White Goods
- Power Infrastructure
- Factory Automation

### Device Information <sup>(1)</sup>

PART NUMBER	PACKAGE	BODY SIZE (NOM)
AOS138	SOP16	9.90mm × 3.91mm
	TSSOP16	5.00mm × 4.40mm

(1)For all available packages, see the orderable addendum at the end of the data sheet.



## PACKAGE/ORDERING INFORMATION<sup>(1)</sup>


PRODUCT	ORDERING NUMBER	TEMPERATURE RANGE	PACKAGE LEAD	PACKAGE MARKING <sup>(2)</sup>	MSL <sup>(3)</sup>	PACKAGE OPTION
AOS138	AOS138XTSS16	-40°C~+125°C	TSSOP16	AOS138	MSL3	Tape and Reel , 4000
	AOS138XS16-G	-40°C~+125°C	SOP16	AOS138	MSL1	Tape and Reel , 4000
	AOS138XTSS16-G	-40°C~+125°C	TSSOP16	AOS138	MSL1	Tape and Reel , 4000

### NOTE:

- (1) This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the right-hand navigation.
- (2) There may be additional marking, which relates to the lot trace code information (data code and vendor code), the logo or the environmental category on the device.
- (3) MSL, The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications.



PIN CONFIGURATIONS



PIN DESCRIPTION

PIN	NAME	I/O TYPE <sup>(1)</sup>	FUNCTION
SOP16/TSSOP16			
1	A0	I	Address input
2	A1	I	Address input
3	A2	I	Address input
4	E1	I	Enable input (active LOW)
5	E2	I	Enable input (active LOW)
6	E3	I	Enable input (active HIGH)
7	Y7	O	Output
8	GND	-	Ground
9	Y6	O	Output
10	Y5	O	Output
11	Y4	O	Output
12	Y3	O	Output
13	Y2	O	Output
14	Y1	O	Output
15	Y0	O	Output
16	Vcc	-	Power Supply

(1) I=input, O=output.



## SPECIFICATIONS

## Absolute Maximum Ratings

Over operating free-air temperature range (unless otherwise noted)<sup>(1)(2)</sup>

		MIN	MAX	UNIT
V <sub>CC</sub>	Supply voltage range	-0.5	7	V
I <sub>IK</sub>	Input clamp diode current	For V <sub>I</sub> < 0.5V or V <sub>I</sub> > V <sub>CC</sub> +0.5V	± 20	mA
I <sub>OK</sub>	Output clamp diode current	For V <sub>O</sub> < -0.5V or V <sub>O</sub> > V <sub>CC</sub> +0.5V	± 20	mA
I <sub>O</sub>	Output source or sink current per output pin	For V <sub>O</sub> > -0.5V or V <sub>O</sub> < V <sub>CC</sub> +0.5V	± 25	mA
	Continuous current through V <sub>CC</sub> or GND		± 50	mA
J <sub>A</sub>	Package thermal impedance <sup>(3)</sup>	SOP16	150	°C/W
		TSSOP16	45	
T <sub>J</sub>	Junction temperature <sup>(4)</sup>	-65	150	°C
T <sub>stg</sub>	Storage temperature	-65	150	°C
	Lead temperature (Soldering 10s) (SOIC -Lead Tips Only)		300	°C

- (1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) The input and output negative-voltage ratings may be exceeded if the input and output current ratings are observed.
- (3) The package thermal impedance is calculated in accordance with JESD-51.
- (4) The maximum power dissipation is a function of T<sub>J(MAX)</sub>, R<sub>JA</sub>, and T<sub>A</sub>. The maximum allowable power dissipation at any ambient temperature is P<sub>D</sub>=(T<sub>J(MAX)</sub>-T<sub>A</sub>)/R<sub>JA</sub>. All numbers apply for packages soldered directly onto a PCB.



### ESD Ratings

The following ESD information is provided for handling of ESD-sensitive devices in an ESD protected area only.

			VALUE	UNIT
V <sub>(ESD)</sub>	Electrostatic discharge	Human-Body Model (HBM), per ANSI/ESDA/JEDEC JS-001 <sup>(1)</sup>	± 2000	V
		Charged-Device Model (CDM), per ANSI/ESDA/JEDEC JS-002 <sup>(2)</sup>	± 1000	
		Machine Model (MM)	± 200	

- (1) JEDEC document JEP155 states that 500V HBM allows safe manufacturing with a standard ESD control process.
- (2) JEDEC document JEP157 states that 250V CDM allows safe manufacturing with a standard ESD control process.



### ESD SENSITIVITY CAUTION

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.



Recommended Operating Conditions

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	MAX	UNIT
Supply Voltage	$V_{CC}$		4.5	5.5	V
Input Voltage	$V_I$		0	$V_{CC}$	V
Output Voltage	$V_O$		0	$V_{CC}$	V
Input Rise and Fall Time	$t_t$	$V_{CC}=2V$		1000	ns
		$V_{CC}=4.5V$		500	
		$V_{CC}=5.5V$		400	
Operating Temperature	$T_A$		-40	125	°C

(1) All unused inputs of the device must be held at  $V_{CC}$  or GND to ensure proper device operation.



Electrical Characteristics

PARAMETER	TEST CONDITIONS <sup>(4)</sup>	V <sub>CC</sub>	Operating free-air temperature (T <sub>A</sub> )									UNIT
			25°C			-40°C to 85°C			-40°C to 125°C			
			MIN <sup>(2)</sup>	TYP <sup>(3)</sup>	MAX <sup>(2)</sup>	MIN <sup>(2)</sup>	TYP <sup>(3)</sup>	MAX <sup>(2)</sup>	MIN <sup>(2)</sup>	TYP <sup>(3)</sup>	MAX <sup>(2)</sup>	
V <sub>IH</sub>		2	1.5			1.5			1.5			V
		4.5	3.15			3.15			3.15			
		5.5	3.85			3.85			3.85			
V <sub>IL</sub>		2			0.5			0.5			0.5	V
		4.5			1.35			1.35			1.35	
		5.5			1.65			1.65			1.65	
V <sub>OH</sub>	I <sub>OH</sub> = -20μA	2	1.9			1.9			1.9			V
	I <sub>OH</sub> = -20μA	4.5	4.4			4.4			4.4			
	I <sub>OH</sub> = -20μA	5.5	5.4			5.4			5.4			
	I <sub>OH</sub> = -4mA	4.5	3.98			3.84			3.7			
	I <sub>OH</sub> = -5.2mA	5.5	4.95			4.81			4.67			
V <sub>OL</sub>	I <sub>OL</sub> = 20μA	2			0.1			0.1			0.1	V
	I <sub>OL</sub> = 20μA	4.5			0.1			0.1			0.1	
	I <sub>OL</sub> = 20μA	5.5			0.1			0.1			0.1	
	I <sub>OL</sub> = 4mA	4.5			0.26			0.33			0.4	
	I <sub>OL</sub> = 5.2mA	5.5			0.26			0.33			0.4	
I <sub>I</sub>	V <sub>I</sub> = V <sub>CC</sub> or GND	5.5			± 0.1			± 1			± 1	μA
I <sub>CC</sub>	V <sub>I</sub> = V <sub>CC</sub> or GND	5.5			8			80			160	μA

- (1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation.
- (2) Limits are 100% production tested at 25°C. Limits over the operating temperature range are ensured through correlations using statistical quality control (SQC) method.
- (3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration.
- (4) V<sub>I</sub> = V<sub>IH</sub> or V<sub>IL</sub>, unless otherwise noted.



Switching Characteristics

Input  $t_i = 6\text{ns}$ .


PARAMETER	TEST CONDITIONS <sup>(4)</sup>	V <sub>CC</sub>	Operating free-air temperature (T <sub>A</sub> )									UNIT
			25°C			-40°C to 85°C			-40°C to 125°C			
			MIN <sup>(2)</sup>	TYP <sup>(3)</sup>	MAX <sup>(2)</sup>	MIN <sup>(2)</sup>	TYP <sup>(3)</sup>	MAX <sup>(2)</sup>	MIN <sup>(2)</sup>	TYP <sup>(3)</sup>	MAX <sup>(2)</sup>	
t <sub>pd</sub>	Address to Output	CL= 50pF	2		51			54			55	ns
			4.5		11	16		18		19		
			5.5			14		16		17		
	Strobe E1, E2, E3 to Output AOS138	CL= 50pF	2		46			49		50		
			4.5			14		15		16		
			5.5			12		13		14		
t <sub>t</sub>	Output Transition Time	CL= 50pF	2		39			41		46		
			4.5			14		16		17		
			5.5			12		13		15		
C <sub>PD</sub>	Power Dissipation Capacitance <sup>(4)</sup>	CL= 15pF	5		67						pF	
C <sub>i</sub>	Input Capacitance				10			10		10		

- (1) All unused inputs of the device must be held at V<sub>CC</sub> or GND to ensure proper device operation.
- (2) This parameter is ensured by design and/or characterization and is not tested in production.
- (3) Typical values represent the most likely parametric norm as determined at the time of characterization. Actual typical values may vary over time and will also depend on the application and configuration.
- (4) C<sub>PD</sub> is used to determine the dynamic power consumption, per gate.




PARAMETER MEASUREMENT INFORMATION

Phase relationships between waveforms were chosen arbitrarily. All input pulses are supplied by generators having the following characteristics:  $PRR \leq 1 \text{ MHz}$ ,  $Z_0 = 50 \Omega$ ,  $t_t < 6 \text{ ns}$ . For clock inputs,  $f_{max}$  is measured when the input duty cycle is 50%. The outputs are measured one at a time with one input transition per measurement.



(1)  $C_L$  includes probe and test-fixture capacitance.


Figure 1. Load Circuit for Push-Pull Outputs



(1) The greater between  $t_{PLH}$  and  $t_{PHL}$  is the same as  $t_{pd}$ .


(1) The greater between  $t_{PLH}$  and  $t_{PHL}$  is the same as  $t_{pd}$ .

Figure 2. Voltage Waveforms, Propagation Delays for Standard CMOS Inputs



(1) The greater between  $t_{PLH}$  and  $t_{PHL}$  is the same as  $t_{pd}$ .

Figure 4. Voltage Waveforms, Propagation Delays for TTL-Compatible Inputs



(1) The greater between  $t_r$  and  $t_f$  is the same as  $t_t$ .

Figure 3. Voltage Waveforms, Input and Output Transition Times for Standard CMOS Inputs



DETAILED DESCRIPTION

Overview

The AOS138 device is 3-to-8 decoders/demultiplexers. The three address input pins, A0, A1, and A2, select which output is active. The selected output is pulled LOW, while the remaining outputs are all HIGH. The conditions at the binary weighted inputs at the three enable inputs select one of eight output lines. The three enable input pins, E3, E2 and E1. One active high enable and two active low enable pins are available, and any enable pin can be deactivated to force all outputs high. All three enable pins must be active for the output to be enabled.

Functional Block Diagram




Figure 5. Functional Block Diagram



Device Functional Modes

Device Function Table

ENABLE INPUTS			ADDRESS INPUTS			OUTPUTS							
E3	E2	E1	A2	A1	A0	Y0	Y1	Y2	Y3	Y4	Y5	Y6	Y7
X	H	X	X	X	X	H	H	H	H	H	H	H	H
X	X	H	X	X	X	H	H	H	H	H	H	H	H
L	X	X	X	X	X	H	H	H	H	H	H	H	H
H	L	L	L	L	L	L	H	H	H	H	H	H	H
H	L	L	L	L	H	H	L	H	H	H	H	H	H
H	L	L	L	H	L	H	H	L	H	H	H	H	H
H	L	L	L	H	H	H	H	H	L	H	H	H	H
H	L	L	H	L	L	H	H	H	H	L	H	H	H
H	L	L	H	L	H	H	H	H	H	H	L	H	H
H	L	L	H	H	L	H	H	H	H	H	H	L	H
H	L	L	H	H	H	H	H	H	H	H	H	H	L

H: High Voltage Level  
L: Low Voltage Level  
X: Don't care



### POWER SUPPLY RECOMMENDATIONS

The power supply pin should have a good bypass capacitor to prevent power disturbance. For devices with a single supply, a 0.1 $\mu$ F capacitor is recommended and if there are multiple V<sub>CC</sub> terminals then 0.01 $\mu$ F or 0.022 $\mu$ F capacitors are recommended for each power terminal. It is acceptable to parallel multiple bypass caps to reject different frequencies of noise. The 0.1 $\mu$ F and 1 $\mu$ F capacitors are commonly used in parallel. The bypass capacitor should be installed as close to the power terminal as possible.

### LAYOUT

#### Layout Guidelines

When using multiple bit logic devices inputs should not ever float. In many cases, functions or parts of functions of digital logic devices are unused; for example, when only two inputs of a triple-input AND gate are used or only 3 of the 4 buffer gates are used. Such input pins should not be left unconnected because the undefined voltages at the outside connections result in undefined operational states. Specified below are the rules that must be observed under all circumstances. All unused inputs of digital logic devices must be connected to a high or low bias to prevent them from floating. The logic level that should be applied to any particular unused input depends on the function of the device. Generally, they will be tied to GND or VCC whichever make more sense or is more convenient.

#### Layout Example






Figure 6. Layout Diagram



PACKAGE OUTLINE DIMENSIONS  
SOP16<sup>(3)</sup>




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A <sup>(1)</sup>	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D <sup>(1)</sup>	9.800	10.200	0.386	0.402
E <sup>(1)</sup>	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270(BSC) <sup>(2)</sup>		0.050(BSC) <sup>(2)</sup>	
L	0.400	1.270	0.016	0.050
	0°	8°	0°	8°

NOTE:

1. Plastic or metal protrusions of 0.15mm maximum per side are not included.
2. BSC (Basic Spacing between Centers), "Basic" spacing is nominal.
3. This drawing is subject to change without notice.



TSSOP16<sup>(3)</sup>




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A <sup>(1)</sup>		1.200		0.047
A1	0.050	0.150	0.002	0.006
A2	0.800	1.050	0.031	0.041
b	0.190	0.300	0.007	0.012
c	0.090	0.200	0.004	0.008
D <sup>(1)</sup>	4.860	5.100	0.191	0.201
E <sup>(1)</sup>	4.300	4.500	0.169	0.177
E1	6.200	6.600	0.244	0.260
e	0.650(BSC) <sup>(2)</sup>		0.026(BSC) <sup>(2)</sup>	
L	0.500	0.700	0.02	0.028
H	0.250 TYP		0.010 TYP	
	1°	7°	1°	7°

NOTE:

1. Plastic or metal protrusions of 0.15mm maximum per side are not included.
2. BSC (Basic Spacing between Centers), "Basic" spacing is nominal.
3. This drawing is subject to change without notice.



**TAPE AND REEL INFORMATION**



NOTE: The picture is only for reference. Please make the object as the standard.

**KEY PARAMETER LIST OF TAPE AND REEL**

Package Type	Reel Diameter	Reel Width(mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
SOP16	13''	16.4	6.50	10.30	2.10	4.0	8.0	2.0	16.0	Q1
TSSOP16	13''	12.4	6.90	5.60	1.20	4.0	8.0	2.0	12.0	Q1

NOTE:

1. All dimensions are nominal.
2. Plastic or metal protrusions of 0.15mm maximum per side are not included.